

BYM	DESCRIPTION	DATE	APPROV.
A	.125 WAS .125 MAX, .413 WAS .413 MAX	11-25-69	11-26-69

DRAWN BY GARCIA	
DATE	6-12-69
CHECKED	QDA
DATE	6-12-69
APPD.	
DATE	
APPD.	
DATE	

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES	
FRACTIONS	TOLERANCES ON DECIMALS
± 1/64	± .005
	ANGLES ± 1°
MATERIAL: STEEL A151 4037	
TENSILE	85,000 PSI MIN.
FINISH:	CAD FIT. DQ-F-466.
CL. 2, TYPE 1	
GRIP RANGE: SEE CHART	

TITLE	
RIVNUT®	
5/16-24 THREAD	
UNLOCK, 100° CS'K HEAD	
SCALE	NONE
WT. ACT.	
DWG. SIZE	A
ISSUE	A
SHEET	1 OF 1
CODE IDENT. NO.	03481
DEPT.	1807
B.F. GOODRICH	
AEROSPACE AND DEFENSE PRODUCTS	
A DIVISION OF THE B.F. GOODRICH CO.	
AKRON, OHIO	

FOR INSTALLATION TOOL:
FOR C-362 TOOL USE SPECIAL PULL UP STUD
P/N P-147-3124L

RIVNUT PART N ^o .	RANGE	GRIP IDENT.	GRIP IDENT.
2R1502	.075 - .151	BLANK	.594
2R1502-1	.151 - .226	1 RAD	.672

